

WATER HEATING SOLUTIONS DESIGNED FOR MULTI-FAMILY PROPERTY OWNERS, BUILDERS, AND MRO

## NEW RHEEM LOWBOYS WITH SIDE CONNECTIONS


IDEAL FOR MULTI-FAMILY PROPERTIES & TIGHT INSTALLATION SPACES

## **FLEXIBLE INSTALLATION**

- Best in class diameter\*- 19.75" diameter unit passes through tight 20" entryways such as small utility closets and attic openings without having to remove doors
- **Side water connections** allow easy like for like replacement and reduce installed height

## HIGH PERFORMANCE. EASY TO SERVICE.

- Best in class performance\*- highest first hour hot water delivery amongst competitors
- Front facing serviceable components streamline maintenance
- Rheemglas® tank lining resists corrosion and prolongs tank life
- EverKleen® helix device reduces sediment improving efficiency and tank life
- 6-Year limited tank and parts warranty





Rheem Side Connect Lowboy

	Rheem Lowboy Side Connect PROE28 S2 RH93 SB	Competitor A 30-Gallon	Rheem Lowboy Side Connect PROE38 S2 RH93 SB	Competitor A 40-Gallon
Nominal Capacity (gal.)	28	28	38	38
Height	30	30	31.5	31.75
Wattage	4500	4500	4500	4500
Uniform Energy Factor (UEF)	0.92	0.90	0.94	0.94
First Hour Rating (FHR)	48	47	55	57
Diameter (No Blanket)	19.75	22	23	24
Ship Weight (lbs)	97	101	128	118
EverKleen Helix Device	Yes	No	Yes	No

<sup>\*</sup>For 4500 watt models, Rheem has the best in class FHR and diameter measurements for 30-gallon tanks.

